

MATTE PAINT CARE

Congratulations on your purchase of our Matte Paint Prescription. You now have everything needed to properly maintain a perfect no-shine finish. On the following pages you'll find detailed instructions for each product; for further information visit the individual product pages on our website. We're always here to help so please don't hesitate to contact us with questions or comments.

GUIDELINES

- Always keep your matte paint protected.
- Hand wash on a regular basis.
- Do not use polish or wax on the finish.

www.drbeasleys.com/matte-paint-prescription.html

FIRST TIME USE

In order to keep your matte paint looking as close to factory finish as possible, you should start off by doing two things...

① **Wash Vehicle**
by hand using Matte Body Wash. Do not dry.

② **Protect Finish**
with Matte Paint Sealant.
Dry with a clean microfiber towel.

MORE INFO...

MATTE BODY WASH

- 1 Add Matte Body Wash to empty bucket. (Dilution: 2 generous capfuls of soap per gallon of water used)
- 2 Add water and agitate with wash pad to generate suds.
- 3 Thoroughly rinse the vehicle.
- 4 Begin washing from top to bottom, section by section. Rinse wash pads often to remove dirt.
- 5 After the vehicle has been thoroughly washed, rinse until all foam and suds are removed
- 6 Dry vehicle with soft, clean microfiber towels. (If following with Matt Paint Sealant do not dry)

TIP Wash car at least twice per month to keep finish clean.

www.drbeasleys.com/matte-body-wash.html



MATTE PAINT SEALANT

- 1 Rinse car before applying Matte Paint Sealant. Matte Paint Sealant should only be applied to a wet surface.
- 2 Apply 8-10 drops of the sealant to a clean foam applicator and begin to apply to the surface. Use overlapping strokes to ensure full coverage.
- 3 Apply to one panel at a time. Remove with a microfiber towel before proceeding. There is no need to let cure. Add extra drops of product to applicator as needed.
- 4 Matte Paint Sealant can be applied right over emblems, door handles, and badging for added protection.
- 5 Reapply every 6-9 months, or as needed.

TIP A little goes a long way. One ounce of product is all that is needed for most cars.

www.drbeasleys.com/matte-paint-sealant.html



MATTE PAINT CLEANSER

- ① Identify heavily soiled area of vehicle. This may include heavy dirt, waterspots, overspray, or hard to remove insect remains.
- ② Spray area directly with Matte Paint Cleanser. Allow to sit on the surface for 1-2 minutes before gently wiping with a microfiber towel. Do not allow to dry.
- ③ Several applications/more dwell time may be necessary for tougher to clean areas. Do not scrub or use unnecessary pressure on the paint surface. Let the product work on the surface to break down contaminants on its own.
- ④ After wiping clean, rinse and reapply Matte Paint Sealant to that specific area. Matte Paint Cleanser can remove existing layer of sealant, so reapplication is recommended.

TIP Matte Paint Cleanser is also a great “prep step” before applying Matte Paint Sealant.

www.drbeasleys.com/matte-paint-cleanser.html



MATTE FINAL FINISH

- ① Identify lightly soiled area of vehicle. This may include dust, bird droppings, or finger prints.
- ② Lightly mist the area with Matte Final Finish.
- ③ Wipe gently with a microfiber cloth in long horizontal strokes to remove the product.
- ④ Continue around the vehicle until all problems have been addressed.
- ⑤ Matte Final Finish is not a replacement for Matte Paint Cleanser. It will not remove embedded debris, staining, or etching.

TIP Always keep Matte Final Finish handy. You never know when you'll run into messes.

www.drbeasleys.com/matte-final-finish.html

