



Dr_x Beasley'sTM

Safety Data Sheet Leather Lock Pro

SECTION 1: Identification

GHS Product identifier

Product name	Leather Lock Pro
Product number	ik18-2
Brand	Dr. Beasley's

Recommended use of the chemical and restrictions on use

Water repellent for top coated leathers

Supplier's details

Name	Dr. Beasley's
Address	1439 W Shakespeare Ave Chicago IL 60614 US

Telephone	773-404-1600
-----------	--------------

Emergency phone number

CHEMTREC 24 Hours/day; 7 Days/week
USA and Canada - Toll Free: 800-424-9300
USA and Canada - Local: +1-703- 527-3887

SECTION 2: Hazard identification

Classification of the substance or mixture

GHS classification in accordance with: OSHA (29 CFR 1910.1200, 2024)

- Flammable liquids, Cat. 3
- Aspiration hazard, Cat. 1

GHS label elements, including precautionary statements

Pictograms



Signal word

Danger

Safety Data Sheet

Leather Lock Pro

Hazard statement(s)

H226

Flammable liquid and vapor

H304

May be fatal if swallowed and enters airways

Precautionary statement(s)

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233

Keep container tightly closed.

P240

Ground and bond container and receiving equipment.

P241

Use explosion-proof electrical/ventilating/lighting/equipment.

P242

Use non-sparking tools.

P243

Take action to prevent static discharges.

P280

Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/...

P301+P310

IF SWALLOWED: Immediately call a POISON CENTER or doctor.

P303+P361+P353

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P331

Do NOT induce vomiting.

P370+P378

In case of fire: Use appropriate method to extinguish.

P403+P235

Store in a well-ventilated place. Keep cool.

P405

Store locked up.

P501

Dispose of contents/container in accordance with local/regional/national/international regulations.

SECTION 3: Composition/information on ingredients

Mixtures

Component	Concentration
Naphtha (petroleum) hydrotreated heavy (CAS no.: 64742-48-9)	80 - 100 % (weight)*
Proprietary Polymers	0.5 - 1.5 % (weight)*

Trade secret statement (OSHA 1910.1200(i))

*The specific chemical identities and/or actual concentrations or actual concentration ranges for one or more listed components are being withheld as trade secrets under the US regulation 29 CFR 1910.1200(i).

SECTION 4: First-aid measures

Description of necessary first-aid measures

If inhaled

Remove to fresh air and promote deep breathing. Get medical attention if effects persist.

Acute and delayed symptoms and effects: May cause respiratory irritation. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

In case of skin contact

Take off immediately all contaminated clothing. Wash with plenty of soap and water. Get medical attention if irritation develops or persists.

Acute and delayed symptoms and effects: May cause skin irritation. Signs/symptoms may include localized redness, swelling, and itching.

Safety Data Sheet

Leather Lock Pro

In case of eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation persists, get medical attention

Acute and delayed symptoms and effects: May cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

If swallowed

Do not induce vomiting. Do not give liquids. Obtain emergency medical attention.

Acute and delayed symptoms and effects: Aspiration hazard. May cause gastrointestinal irritation. Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Most important symptoms/effects, acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11

Indication of immediate medical attention and special treatment needed, if necessary

Symptoms may not appear immediately. Seek medical attention if effects persist and you feel unwell.

SECTION 5: Fire-fighting measures

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Specific hazards arising from the chemical

Carbon oxides

Special protective actions for fire-fighters

Wear self-contained breathing apparatus for firefighting if necessary.

Further information

Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

For Non-Emergency Personnel: Evacuate the area and keep unauthorized individuals away. Avoid breathing vapors or mist, and ensure adequate ventilation. Eliminate all sources of ignition, such as smoking, sparks, or open flames. Take steps to prevent static discharges and use only non-sparking tools and explosion-proof equipment. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

Environmental precautions

Do not let product enter drains.

Methods and materials for containment and cleaning up

Cover drains. Eliminate all sources of ignition. Contain the spill using inert absorbent materials. Collect the material and place it into tightly sealed, labeled containers for proper disposal according to local regulations. Use only non-sparking tools for containment and cleanup to reduce the risk of ignition. Ensure all handling equipment is grounded and bonded to prevent static discharges.

Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

Precautions for safe handling

Handle the product in a well-ventilated area to minimize vapor exposure and avoid breathing vapors, mist, or spray. Use only explosion-proof equipment and non-sparking tools, and ground and bond containers and equipment to prevent static discharge. Keep the product away from heat, sparks, open flames, and other sources of ignition. Smoking is prohibited in the handling area. Avoid contact with eyes, skin, and clothing, and wash hands thoroughly after handling. Ensure containers are tightly closed when not in use to prevent leaks and spills. Follow good industrial hygiene practices and use appropriate personal protective equipment as specified in Section 8.

Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well-ventilated area away from heat, sunlight, and ignition sources. Keep containers sealed and use approved storage for flammable liquids. Avoid storing near oxidizers or other incompatible materials.

Specific end use(s)

Apart from the uses mentioned in section 1 no other specific uses are stipulated.

SECTION 8: Exposure controls/personal protection

Control parameters

CAS: 64742-48-9 (EC: 265-150-3)

Naphtha (petroleum) hydrotreated heavy

OSHA: 400 mg/m³ / 100 ppm PEL-TWA inhalation [Naphtha (petroleum), hydrotreated heavy]

Appropriate engineering controls

Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, gas, etc.) below recommended exposure limits.

Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection

Safety glasses are recommended if splash hazard.

Skin protection

Wear protective gloves, such as nitrile gloves.

Body protection

Wear suitable protective clothing.

Respiratory protection

Provide good ventilation. Respiratory protection is not required under normal use conditions.

SECTION 9: Physical and chemical properties

Basic physical and chemical properties

Physical state

Liquid

Color

Clear

Odor

Solvent

Melting point/freezing point

No data available.

Boiling point or initial boiling point and boiling range

Estimate: 128-188 °C (262.4 -370° F)

Flammability

Flammable

Lower and upper explosion limit/flammability limit

Estimate: LEL: 0.7 UEL:5.4

Flash point

Estimate: 43-46°C (110-114°F)

Safety Data Sheet

Leather Lock Pro

Auto-ignition temperature	Estimate: 290-330°C (554-626°F)
Decomposition temperature	No data available.
pH	No data available.
Kinematic viscosity	No data available.
Solubility	Negligible
Partition coefficient n-octanol/water (log value)	No data available.
Vapor pressure	Estimate: 1.075 kPa (0.56 mm Hg) at 24C
Density and/or relative density	(H2O=1) NA
Relative vapor density	(Air=1.0): >1
Particle characteristics	No data available.

SECTION 10: Stability and reactivity

Reactivity

None under normal use conditions.

Chemical stability

Stable under normal storage conditions.

Possibility of hazardous reactions

No data available.

Conditions to avoid

Heat, flames and sparks. Incompatible products. Keep away from open flames, hot surfaces and sources of ignition.

Incompatible materials

Strong oxidizing agents

Hazardous decomposition products

Other decomposition products - No data available

In the event of fire: see section 5

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity

Components:

Likely Routes of Exposure: Eye contact. Skin contact. Inhalation. Ingestion.

Based on available data, classification data are not met

Acute and delayed symptoms and effects from inhalation, skin and eye contact and ingestion are listed in Section 4.

Skin corrosion/irritation

Based on available data, classification data are not met

Serious eye damage/irritation

Based on available data, classification data are not met

Respiratory or skin sensitization

Based on available data, classification data are not met

Germ cell mutagenicity

Based on available data, classification data are not met

Safety Data Sheet

Leather Lock Pro

Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity

Based on available data, classification data are not met

Specific target organ toxicity (STOT) - single exposure

Based on available data, classification data are not met

Specific target organ toxicity (STOT) - repeated exposure

Based on available data, classification data are not met

Aspiration hazard

May be fatal if swallowed and enters airways

SECTION 12: Ecological information

Toxicity

No data available on product.

Persistence and degradability

No data available on product.

Bioaccumulative potential

No data available on product.

Mobility in soil

No data available on product.

Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

Other adverse effects

No data available on product.

SECTION 13: Disposal considerations

Disposal methods

Product disposal

Disposal should be in accordance with applicable Federal, State and local laws and regulations. Local regulations may be more stringent than State or Federal requirements.

Packaging disposal

Dispose of as unused product.

SECTION 14: Transport information

DOT (US)

UN Number: 1268

Class: 3

Packing Group: III

Proper Shipping Name: PETROLEUM DISTILLATES, N.O.S

Marine pollutant: No

Poison inhalation hazard: No

IMDG

UN Number: 1268

Class: 3

Packing Group: III

EMS Number: F-E, S-E

Proper Shipping Name: PETROLEUM DISTILLATES, N.O.S

IATA

UN Number: 1268

Class: 3

Packing Group: III

Proper Shipping Name: PETROLEUM DISTILLATES, N.O.S

SECTION 15: Regulatory information

Safety, health and environmental regulations specific for the product in question

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard

Massachusetts Right To Know Components

No components are subject to the Massachusetts Right to Know Act.

New Jersey Right To Know Components

No components are subject to the New Jersey Right to Know Act.

Pennsylvania Right To Know Components

No components are subject to the Pennsylvania Right To Know Act.

California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

SECTION 16: Other information

Further information/disclaimer

DISCLAIMER: The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigation to determine the suitability of information for their particular purposes. In no event shall DR. BEASLEY'S, INC. be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, whatsoever arising, even if DR. BEASLEY'S, INC. has been advised of the possibility of such damages.