

CAR POLISHING CHECKLIST

The following checklist assumes you have already washed the vehicle thoroughly and begins with paintwork inspection for contamination. While these instructions are written for those using a free-spinning random orbital polisher, gear-driven orbital and rotary polishers may also be used.

SUPPLIES

- | | |
|--|---|
| ☐ RANDOM ORBITAL POLISHER | ☐ SANDWICH BAGGIE |
| ☐ 12 GAUGE POWER CORD | ☐ STRONG INSPECTION LIGHT |
| ☐ CUTTING, POLISHING & FINISHING PADS | ☐ PAINTER'S TAPE |
| ☐ POLISH, COMPOUND & AIO | ☐ CERAMIC COATING |
| ☐ CLEAN MICROFIBER TOWELS | ☐ IPA OR PANEL WIPE (FOR ORGANIC POLISH) |
| ☐ CLAY BAR & CLAY LUBE | ☐ CERAMIC MAINTENANCE SPRAY |

STANDARD OPERATING PROCEDURES

- | | |
|---|--|
| ☐ MOVE VEHICLE INSIDE OR OUT OF SUN | ☐ 3C. INCREASE SPEED & COUNT PASSES |
| ☐ ENSURE WORK SPACE IS CLEAN | ☐ 4. INSPECT & REPEAT IF RESULTS GOOD |
| ☐ REMOVE ALL JEWELRY & WATCHES | ☐ 6. BUFF ROOF |
| ☐ ENSURE VEHICLE IS COOL TO TOUCH | ☐ 7. BUFF HOOD |
| ☐ 1. BAGGIE TEST FOR CONTAMINATION | ☐ 8. BUFF TRUNKLID |
| ☐ 2. DECONTAMINATE PAINT IF NEEDED | ☐ 9. BUFF VERTICAL PANELS |
| ☐ 3. PERFORM TEST SPOT IN SMALL AREA | ☐ 10. WIPE AWAY OR REMOVE OILS WITH IPA |
| ☐ 3A. APPLY 3-4 DIME SIZE DROPS TO PAD | ☐ 11. APPLY CERAMIC COATING |
| ☐ 3B. SPREAD PRODUCT OUT AT LOW SPEED | ☐ 12. MAINTAIN WITH CERAMIC SPRAY |