



CERAMIC COATING APPLICATION CHECKLIST

The following checklist is written to be used with Dr. Beasley's Nano-Resin Kit. If using a different ceramic coating, refer to the manufacturer instructions for the most accurate and complete application guide.

SUPPLIES

- CERAMIC COATING KIT
- INSPECTION LIGHT
- PAINTER'S TAPE
- CLEAN MICROFIBER TOWELS

STANDARD OPERATING PROCEDURES

- | | |
|---|---|
| <input type="checkbox"/> 1. APPLY BUILDER IN 2'X2' SECTIONS | <input type="checkbox"/> 10. REPEAT 4-9 ACROSS VEHICLE |
| <input type="checkbox"/> 2. LET DWELL FOR 2-3 MINUTES | <input type="checkbox"/> LEAVE VEHICLE UNDISTURBED FOR 1 HOUR |
| <input type="checkbox"/> 3. REMOVE WITH MICROFIBER TOWEL | <input type="checkbox"/> AVOID GETTING WET FOR 24-48 HOURS |
| <input type="checkbox"/> 4. PRIME APPLICATOR WITH COATING | <input type="checkbox"/> DO NOT WASH FOR 1 WEEK |
| <input type="checkbox"/> 5. APPLY COATING TO 20"X20" AREA | |
| <input type="checkbox"/> 6. LET SIT FOR 45 SEC - 1 MIN | |
| <input type="checkbox"/> 7. LEVEL & BUFF OFF WITH TOWEL | |
| <input type="checkbox"/> 8. INSPECT SECTION FOR HIGH SPOTS | |
| <input type="checkbox"/> 9. REMOVE HIGH SPOTS IF NECESSARY | |

SEE PART 3 FOR MAINTENANCE INSTRUCTIONS